

Models	2060 / 2085	2081E	3216 E/EP	4016 E/EP	5032 E/EP	6542 E/EP
<b>Lift Capacity</b>	2,000 lb	2,000 lb	3,200 lb	4,000 lb	5,000 lb	6,500 lb
<b>Reach</b>	5 ft / 10.5 ft	11 ft	16.5 ft	16.5 ft	21 ft	21 ft
<b>Ft-Lb Rating</b>	6,000 / 8,500	8,500	12,500	18,500	30,000	40,000
<b>Extension (Hyd or Man)</b>	M	M	H / M	H / M	H	H
<b>Degree of Rotation</b>	Continuous	400	400	400	400	400
<b>Proportional Control</b>	No	No	No/Yes	No/Yes	No/Yes	No/Yes
<b>Operating Weight</b>	280 lb / 350 lb	425 lb	750 lb	750 lb	1,445 lb	1,500 lb
<b>Recommended Outrigger</b>	11,000 ft-lb	11,000 ft-lb	20,000 ft-lb	20,000 ft-lb	30,000 ft-lb	43,000 ft-lb

Models	5032	6542	6543	8652	8653	1061	1069	1593
<b>Lift Capacity</b>	5,000 lb	6,500 lb	6,500 lb	8,600 lb	8,600 lb	11,000 lb	11,000 lb	14,800 lb
<b>Reach</b>	21 ft	21 ft	30.5 ft	21.5 ft	30.5 ft	21 ft	29 ft	30.5 ft
<b>Ft-Lb Rating</b>	30,000	40,000	43,000	53,000	50,000	66,000	75,000	90,000
<b>Extension (Hyd or Man)</b>	H	H	H	H	H	H	H	H
<b>Degree of Rotation</b>	400	400	400	400	400	400	400	400
<b>Proportional Control</b>	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
<b>Operating Weight</b>	1,420 lb	1,450 lb	1,920 lb	1,650 lb	1,950 lb	2,070 lb	2,725 lb	3,000 lb
<b>Recommended Outrigger</b>	30,000 ft-lb	43,000 ft-lb	43,000 ft-lb	53,000 ft-lb	53,000 ft-lb	90,000 ft-lb	90,000 ft-lb	90,000 ft-lb
<b>Hydraulic Requirements</b>	8 gpm@ 2875 psi	8 gpm@ 2875 psi	8 gpm@ 2715 psi	8 gpm@ 2765 psi	8 gpm@ 2765 psi	10 gpm@ 2775 psi	10 gpm@ 3000 psi	8 gpm@ 2765 psi